

BRILLION SEEDBED MULCH TUCKER

The Brillion Mulch Tucker is the ideal tool for the operator who needs to anchor mulch over new seedings. The notched "Tucker Blades" push the hay or straw mulch into the soil on newly seeded areas. The rear roller firms up the seedbed and locks the mulch in place to prevent blowing or washing away. Approximate Set Up Time: 1/2 hour.

SPECIFICATIONS:

Frame: 4" x 4" steel tubing

Axles 1-1/2" square axles on "Tucker Blades," 4" O.D.
Pipe axles on pulverizer section.

Bearings: Triple sealed, self aligning, flanged bearings.

Tucker Blades: Notched, 20" diameter, 3/16" abrasive resistant steel
on 8" spacings.

Pulverizer Roller: 16" diameter, cast iron, notched wheels.

Hitch: 6' Model - Category I Three Point Hitch
8' Model - Category I and II Three Point Hitch

Dimensions:	SMT-6 Overall width: 80"	Working width: 72"
	Length: 46"	Height: 41"
	SMT-8 Overall width: 104"	Working width: 96"
	Length: 46"	Height: 41"

Tractor Requirements for SMT-8: Minimum 30 Horsepower with lift capacity of 2,000 lbs. located 24" behind the hitch.



Model	Description	Approx. Weight	Suggested List Price
SMT-6	Seedbed Mulch Tucker (6' Roller Width)	1340 lbs.	
SMT-8	Seedbed Mulch Tucker (8' Roller Width)	1600 lbs.	
T6	6' Tucker Assembly Only	404 lbs.	
T8	8' Tucker Assembly Only	491 lbs.	